



# ICD 12.1" Industrial Monitor

Self-Service ■ Kiosk ■ Industrial ■ Public Spaces

## Features

Rugged & Durable

Fully Customizable

Versatile  
Mounting Design

Aluminum Alloy  
Front Bezel

Multiple  
Interface Options

Highly Responsive and  
Accurate Touch Screen



The high performance, touch-enabled ICD (Industrial Chassis Design) Monitor can adapt seamlessly into almost any environment allowing for easy customization to meet specific design requirements. Ideal for self-service stations, point-of-sale, kiosks, terminals, public spaces and industrial automation, the rugged ICD monitor's user-friendly interface delivers exceptional performance and efficiency.

## Self-Service Station

Increase sales and customer satisfaction, while reducing manpower, by allowing customers to create a customized solution.

## Public Spaces

Designed for continuous use, this interactive touch monitor can withstand typical abuse found in public areas and adapts well to almost any environment.

## Industrial Manufacturing

Impervious to the environmental elements while providing real-time information and continuously reducing data entry time on the factory floor.

## Specifications

<b>Viewable Image Size</b>	12.1"
<b>Color</b>	Black
<b>Pixel Pitch</b>	0.3075 mm
<b>Brightness</b>	300 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	500:1
<b>Viewing Angle</b>	65° Vertical, 55° Horizontal
<b>Response Time</b>	50 ms
<b>Aspect Ratio</b>	4:3
<b>Vertical Synchronization</b>	75 Hz
<b>Touch Screen (Fully Integrated)</b>	5-Wire Resistive
<b>Connectivity Interfaces</b>	2 USB Ports, VGA (DB 15), DVI, S-Video (Option)
<b>PC Compatibility (Touch Driver)</b>	Windows 7, Vista, XP, 2000, Server 2003, 95, 98, ME, NT4, CE 2.12, 3.0, .Net (4.0, 5.0, 6.0); Linux (up to Kernel 2.6); MS DOS; iMac 9.0 / OS X (Power PC, Intel CPU); QNX
<b>Display Resolution</b>	800 x 600 @ 60 Hz
<b>Voltage Rating</b>	AC Input, 100-240V @ 50-60 HZ, External Adaptor
<b>Power Consumption</b>	7.52 W
<b>Dimensions (WxHxD)</b>	329mm x 268mm x 65.9mm
<b>VESA Hole Configuration</b>	75mm x 75mm / 100mm x 100mm
<b>Limited Warranty</b>	1 Year Parts and Labor Including Backlight
<b>Standards</b>	FCC Class A, CE
<b>Operating Temperature</b>	32°F ~ 104°F (0°C ~ 40°)
<b>Storage Temperature</b>	-4°F ~ 140°F (-20°C ~ 60°C)

## Contact Us

220 Tradesmen Dr.  
Hutto, Texas 78634  
1-800-320-5944

Sales@touchsystems.com  
www.touchsystems.com