



TouchSystems

# P20 24" Touch Monitor

Banking ■ Government ■ Information Display ■ Medical

## At a Glance

Four-way  
Ergonomic Stand

Excellent Touch  
Positioning Accuracy

TileMatrix and  
TileComp

1000:1 Contrast Ratio



## Surface Capacitive

P2450C-U - (USB)  
P2450C-S - (Serial)

## Contact Us

220 Tradesmen Dr.  
Hutto, Texas 78634  
1-800-320-5944

Sales@touchsystems.com  
www.touchsystems.com

The P20 24" LCD Touch Monitor offered by TouchSystems tackles even the most demanding, color-critical applications in a wide screen display. With its leading-edge touch technology capabilities and ground breaking design, this monitor can easily be considered the most intelligent visual display solution to date.

## Health Care

From patient check-ins to the operating room, these devices link doctors, nurses, and administrators together with the seamless transfer of information.

## Banking and Finance

Delivering real time information from the trading floor to the bank room lobby, this interactive monitor increases productivity and efficiency.

## Digital Bulletin Boards

Featuring superior, high-end graphics, this touch monitor provides an engaging solution to sharing and displaying up to date information.

## Government Applications

Expediting client services and streamlining data and mail delivery, touch monitors are integrated into public service buildings and government training applications.

## Specifications

Viewable Image Size	24.1"
Color	Black
Pixel Pitch	0.270mm
Brightness	400 cd/m2
Contrast Ratio	1000:1
Viewing Angle	178° Vertical, 178° Horizontal
Response Time	16ms
Aspect Ratio	16:10
Vertical Synchronization	50-85 Hz
Touch Screen (Fully Integrated)	Surface Capacitive
Connectivity Interfaces	USB or Serial (Touch); DVI-I, DVI-D and VGA 15-Pin D-Sub
PC Compatibility (Touch Driver)	Windows 7, Vista, XP, 2000, Server 2003, 95, 98, ME, NT4, CE 2.12, 3.0, .NET (4.0, 5.0, 6.0); Linux (up to Kernel 2.6); MS DOS; iMac 9.0, OS X (Power PC, Intel CPU); QNX
Display Resolution	1920 x 1200@ 60 Hz
Voltage Rating	AC 100-120V / AC 220-240V
Power Consumption	On: 83W; Power Savings Mode: < 1W
Dimensions (WxHxD)	21.8 in. x 17-22.9 x 12 in. (with stand) 21.8 in. x 14.2 in. x 4.1 in. (without stand)
VESA Hole Configuration	100 mm x 100 mm / 200mm x 100mm
Limited Warranty	4 Years Parts and Labor including Backlight
Standards	FCC Class B, CE, UL, Energy Star, RoHS Compliant