



TouchSystems

IndustraTouch Panel PC

Self-Service Station ■ Hospitality Kiosk ■ Point-of-Sale

Features

Rugged & Durable

Fully Customizable

High-Performance
Core 2 Duo Solution

Highly Responsive and
Accurate Touch Screen



Specifications

CPU	Intel Celeron 2.0 GHz up to Core 2 Duo 2.13 GHz
System Chipset	Intel 945 G/ICH7
System Memory	Base 1 GB up to 2 GB Shared DDR, 2 x 240 pin DIMM
Hard Drive	80 GB Hard Drive up to 320 GB
Display	15" TFT LCD, 1024 x 768 Shared Memory Architecture is able to Utilize the Display Memory up to 64 MB
Standard I/O	Serial ports x 4 (COM 1, 2 & 4 with +5V/12V Power Output on Pin 9; COM 2 is Selectable for RS32/422/485; COM 3 is Internal Type Reserved for Touch Screen) Parallel Port x 1 (SPP/EPP/ECP) USB Interface x 2 VGA Interface x 1 DIO: Input x 2, Output x 2
Audio	Speaker x 2 Speaker-out, Line-in & MIC-in
Ethernet	10/100 Base-T with RJ-45 (1G Option) Supports Wake-on-LAN
Power Supply	250W, 100~240V/ 5~3A@50~60Hz

Peripheral & Storage Devices

Expansion Slot	PCI x 2
Touch Screen	Resistive Type or Surface Acoustic Wave (SAW) Type
Drive Bay	Slim CD-ROM or Equivalent Device 3.5" HDD x 1 (Option)

Environmental

Operating Temp	0°C ~ 40°C
Storage Temp	-20°C ~ 60°C
Humidity	5% ~ 80%
Limited Warranty	1 Year including Backlight
Standards	FCC Class A, CE

Contact Us

220 Tradesmen Dr.
Hutto, Texas 78634
1-800-320-5944

Sales@touchsystems.com
www.touchsystems.com