



Specifications

Model	M5-E 17"	M1 19"
Viewable Image Size	17"	19"
Pixel Pitch	0.264mm	0.284mm
Brightness	250 cd/m ²	250 cd/m ²
Contrast Ratio	1000:1	900:1
Viewing Angle	170° Vertical, 170° Horizontal	85°/85°/85°/85° (CR>5)
Response Time	5ms	5ms
Color	Black	Black
Aspect Ratio	4:3	4:3
Vertical Synchronization	56 - 76 Hz	56 - 75 Hz
Touch Screen (Fully Integrated)	Resistive, Surface Capacitive or Surface Acoustic Wave (SAW)	Resistive
Connectivity Interfaces	USB or Serial (Touch); DVI-D and VGA 15-Pin	VGA, DVI-D
PC Compatibility (Touch Driver)	Windows 7, Vista, XP, 2000, Server 2003, 95, 98, ME, NT4, CE 2.12, 3.0, .NET (4.0, 5.0, 6.0); Linux (up to Kernel 2.6); QNX; MS DOS; iMac 9.0, OSX (Power PC, Intel CPU)	Windows 7, Vista, XP, 2000, Server 2003, 95, 98, ME, NT4, CE 2.12, 3.0, .Net (4.0, 5.0, 6.0); Linux (up to Kernel 2.6); MS DOS; iMac 9.0 / OS X (Power PC, Intel CPU); QNX
Display Resolution	1280 x 1024 @ 60 Hz	1280 x 1024 @ 60-75 Hz
Voltage Rating	AC 100-120V / AC 220-240V	AC100-120V / AC 220-240V
Power Consumption	On: 21W / ECO Mode: 0.4W	24W / ECO Mode 1/2: 20W/ 15W / Power Savings Mode: 0.4W
Dimensions (W x H x D)	14.5 x 14.1-16.1 x 9.1 in. (with stand) 14.5 x 12.6 x 2.4 in. (without stand)	16.2 x 15.9 x 8.1 in. (with stand) 16.2 x 13.4 x 2.7 in. (without stand)
VESA Hole Config.	100 x 100mm	100 x 100 mm
Limited Warranty	3 Years Parts and Labor including Backlight	3 Years Parts and Labor including Backlight
Standards	FCC Class B, CE, UL, Energy Star, RoHS	UL /C-UL or CSA, PCT (Gost), C-tick, FCC Class B/Canadian DOC, MPR II / MPR III, PSB, NOM, TUV GS, TUV Ergonomie, CE, GEEA/Energy label, SASO, ISO 9241-307, Pb free, RoHS, EPEAT Silver, ENERGY STAR 5.0 and TCO 5.0 compliant