



M1 19" Touch Monitor

Retail ■ Education ■ Hospitality ■ Corporate ■ Medical

Medical

Link doctors, nurses & administrators together with the seamless transfer of information.

Hospitality Kiosks

Minimize customer wait time with the easy to use design, reinforcing brand awareness & providing eye catching interactive information.

Interactive Learning Stations

Enhance classroom learning, transforming teaching material into an interactive, "hands-on" experience.

Retail Sales

Increase efficiency with its practical design, reduce manpower and exceed the customer's expectations with interactive user interface.

Corporate

Prominently exhibit and edit graphs, charts and information, converting presentations from average to exceptional with this high-performance, touch display.



Resistive

M11990R-UM (USB)
M11990R-SM (Serial)

Contact Us

220 Tradesmen Dr.
Hutto, Texas 78634
1-800-320-5944

Sales@touchsystems.com
www.touchsystems.com

The M1 19" touch monitor has set a new standard in value, offering the advantages of the latest display technologies while delivering an eco-friendly, technology-rich and cost-conscious touch display solutions for several industries.

Specifications

Model	M1 19"
Viewable Image Size	19"
Pixel Pitch	0.284mm
Brightness	250 cd/m ²
Contrast Ratio	900:1
Viewing Angle	85°/85°/85°/85° (CR>5)
Response Time	5ms
Color	Black
Aspect Ratio	
Vertical Synchronization	56 - 75 Hz
Touch Screen (Fully Integrated)	Resistive
Connectivity Interfaces	VGA, DVI-D
PC Compatibility (Touch Driver)	Windows 7, Vista, XP, 2000, Server 2003, 95, 98, ME, NT4, CE 2.12, 3.0, .Net (4.0, 5.0, 6.0); Linux (up to Kernel 2.6); MS DOS; iMac 9.0 / OS X (Power PC, Intel CPU); QNX
Display Resolution	1280 x 1040 @ 60-75 Hz
Voltage Rating	AC100-120V / AC 220-240V
Power Consumption	24W / ECO Mode 1/2: 20W/ 15W / Power Savings Mode: 0.4W
Dimensions (W x H x D)	16.2 x 15.9 x 8.1 in. (with stand) 16.2 x 13.4 x 2.7 in. (without stand)
VESA Hole Config.	100 x 100 mm
Limited Warranty	3 Years Parts and Labor including Backlight
Standards	UL / C-UL or CSA, PCT (Gost), C-tick, FCC Class B/Canadian DOC, MPR II / MPR III, PSB, NOM, TUV GS, TUV Ergonomie, CE, GEEA/Energy label, SASO, ISO 9241-307, Pb free, RoHS, EPEAT Silver, ENERGY STAR 5.0 and TCO 5.0 compliant

