



P20 40" Touch Monitor

Information Display ■ Education ■ Military ■ Corporate

At a Glance

Fast, Accurate
Operation

2000:1 Contrast Ratio

Ultra-Thin Bezel

Multi-User Capability

Finger or Stylus Input



Dispersive Signal Technology

P4050D-U - (USB)
P4050D-S - (Serial)

Protective Overlays

P40PA-20 - (Acrylic)
P40PG - (Chemically
Strengthened Glass)

Contact Us

220 Tradesmen Dr.
Hutto, Texas 78634
1-800-320-5944

Sales@touchsystems.com
www.touchsystems.com

TouchSystems' P20 Touch Monitor series takes the lead in transforming digital signage with maximum impact. This 40" interactive display gives company messages and images the "wow factor" needed to catapult your business to the top. Using Dispersive Signal Technology, for fast, accurate and reliable HD performance, this product is exceptionally durable and impervious to the elements.

Interactive Digital Signage

Catch attention and create impact with this high definition touch display, combining touch and visual interest to increase the effectiveness of your message.

Military Applications

Ideal for military training, these monitors allow complex charts and information to be presented with the touch of a finger.

Educational Learning Stations

Offer a new option in the classroom, creating a more interactive, visually interesting approach to learning.

Corporate Communications

Improve corporate communications by providing a sharp, impactful message on this cutting-edge display.

Specifications

Viewable Image Size	40"
Color	Black
Pixel Pitch	0.648mm
Brightness	700 cd/m ²
Contrast Ratio	2000:1
Viewing Angle	178° Vertical, 178° Horizontal
Response Time	16ms
Aspect Ratio	16:9
Vertical Synchronization	50-85 Hz
Touch Screen (Fully Integrated)	Dispersive Signal Technology (DST)
Connectivity Interfaces	USB or Serial (Touch); DVI-D, Analog D-Sub, Analog BNC, Composite (Shared RCA and BNC), S-Video, HDMI, Composite, Component, Audio
PC Compatibility (Touch Driver)	Windows 7, Vista, XP, Server 2003, CE 2.12, 3.0; .net (4.0, 5.0, 6.0); Linux (up to Kernel 2.6); Mac OS X
Display Resolution	1366 x 768 @ 60 Hz
Voltage Rating	AC 100-120V / AC 220-240V
Power Consumption	On: 240W; Power Savings Mode: < 5W
Dimensions (WxHxD)	36.2 in. x 22.4 in. x 13 in. (with Stand) 36.2 in. x 21 in. x 5.5 in. (without Stand)
VESA Hole Configuration	200 x 200mm (8 hole) / 200 x 100mm (6 hole)
Limited Warranty	3 Years Parts and Labor including Backlight
Standards	FCC Class B, CE, UL, Energy Star, RoHS Compliant