



TouchSystems

P20 20" Touch Monitor

Banking

Corporate

Retail

Medical

At a Glance

Ultra-Thin Bezel

Excellent Touch
Positioning Accuracy

TileMatrix and
TileComp

Portrait Mode



Resistive

P2090R-U - (USB)
P2090R-S - (Serial)

Surface Acoustic Wave (SAW)

P2090S-U - (USB)
P200S-S - (Serial)

Surface Capacitive

P2090C-U - (USB)
P2090C-S - (Serial)

Contact Us

220 Tradesmen Dr.
Hutto, Texas 78634
1-800-320-5944

Sales@touchsystems.com
www.touchsystems.com

Delivering cutting-edge touch technology, the 20" P20 LCD Touch Monitor by Touch Systems offers intelligent and versatile design features, including multi-touch capabilities, gaining admiration from even the most discerning professional users.

Retail Sales

This multi-purpose design enables retailers to reduce manpower, exceed customer expectations and increase sales by promoting, cross-selling and up-selling products and services.

Banking and Finance

Delivering real time information from the trading floor to the bank room lobby, this interactive monitor increases productivity and efficiency.

Health Care

From patient check-ins to the operating room, these devices link doctors, nurses, and administrators together with the seamless transfer of information.

Corporate Solution

Designed to fit into to any environment, this touch screen provides excellent color and quality while being ergonomically friendly.

Specifications

Viewable Image Size	20.1"
Color	Black
Pixel Pitch	0.255mm
Brightness	280 cd/m2
Contrast Ratio	700:1
Viewing Angle	178° Vertical, 178° Horizontal
Response Time	16ms
Aspect Ratio	4:3
Vertical Synchronization	50-85 Hz
Touch Screen (Fully Integrated)	Resistive, Surface Capacitive or Surface Acoustic Wave
Connectivity Interfaces	USB or Serial (Touch); DVI-I, DVI-D and VGA 15 Pin D-Sub
PC Compatibility (Touch Driver)	Windows 7, Vista, XP, 2000, Server 2003, 95, 98, ME, NT4, CE 2.12, 3.0, .NET (4.0, 5.0, 6.0); Linux (up to Kernel 2.6); MS DOS; iMac 9.0, OS X (Power PC, Intel CPU); QNX
Display Resolution	1600 x 1200@ 60 Hz
Voltage Rating	AC 100-120V / AC 220-240V
Power Consumption	On: 50W; Power Savings Mode: < 1W
Dimensions (WxHxD)	17.3 in. x 16.4-22.3 in. x 9.7 in. (with Stand) 17.3 in. x 13.4 in. x 3.3 in. (without Stand)
VESA Hole Configuration	100mm x 100mm
Limited Warranty	4 Years Parts and Labor including Backlight
Standards	FCC Class B, CE, UL, Energy Star, RoHS Compliant