



TouchSystems

P20 24" Touch Monitor

Banking ■ Government ■ Information Display ■ Medical

At a Glance

Four-way Ergonomic Stand

Excellent Touch Positioning Accuracy

TileMatrix and TileComp

1000:1 Contrast Ratio



Surface Capacitive

P2450C-U - (USB)

P2450C-S - (Serial)

Contact Us

220 Tradesmen Dr.

Hutto, Texas 78634

1-800-320-5944

Sales@touchsystems.com

www.touchsystems.com

The P20 24" LCD Touch Monitor offered by TouchSystems tackles even the most demanding, color-critical applications in a wide screen display. With its leading-edge touch technology capabilities and ground breaking design, this monitor can easily be considered the most intelligent visual display solution to date.

Health Care

From patient check-ins to the operating room, these devices link doctors, nurses, and administrators together with the seamless transfer of information.

Banking and Finance

Delivering real time information from the trading floor to the bank room lobby, this interactive monitor increases productivity and efficiency.

Digital Bulletin Boards

Featuring superior, high-end graphics, this touch monitor provides an engaging solution to sharing and displaying up to date information.

Government Applications

Expediting client services and streamlining data and mail delivery, touch monitors are integrated into public service buildings and government training applications.

Specifications

Viewable Image Size	24.1"
Color	Black
Pixel Pitch	0.270mm
Brightness	400 cd/m2
Contrast Ratio	1000:1
Viewing Angle	178° Vertical, 178° Horizontal
Response Time	16ms
Aspect Ratio	16:9
Vertical Synchronization	50-85 Hz
Touch Screen (Fully Integrated)	Surface Capacitive
Connectivity Interfaces	USB or Serial (Touch); DVI-I, DVI-D and VGA 15-Pin D-Sub
PC Compatibility (Touch Driver)	Windows 7, Vista, XP, 2000, Server 2003, 95, 98, ME, NT4, CE 2.12, 3.0, .NET (4.0, 5.0, 6.0); Linux (up to Kernel 2.6); MS DOS; iMac 9.0, OS X (Power PC, Intel CPU); QNX
Display Resolution	1920 x 1200@ 60 Hz
Voltage Rating	AC 100-120V / AC 220-240V
Power Consumption	On: 83W; Power Savings Mode: < 1W
Dimensions (WxHxD)	21.8 in. x 17-22.9 x 12 in. (with stand) 21.8 in. x 14.2 in. x 4.1 in. (without stand)
VESA Hole Configuration	100 mm x 100 mm / 200mm x 100mm
Limited Warranty	4 Years Parts and Labor including Backlight
Standards	FCC Class B, CE, UL, Energy Star, RoHS Compliant