



TouchSystems

P15 32" Touch Monitor

Information Display ■ Education ■ Military ■ Corporate

At a Glance

Landscape and Portrait Orientation

Public-Display-Grade Panel

Excellent Touch Positioning Accuracy

500 cd/m2 Brightness



Dispersive Signal Technology

P3250D-U - (USB)
P3250D-S - (Serial)

Surface Acoustic Wave

P3220S-U - (USB)
P3220S-S - (Serial)

Surface Capacitive

P3250C-U - (USB)
P3250C-S - (Serial)

Protective Overlays

P32PA-15
Acrylic

P32PG-15
Chemically Strengthened Glass

Contact Us

220 Tradesmen Dr.
Hutto, Texas 78634
1-800-320-5944

Sales@touchsystems.com
www.touchsystems.com

Go digital with your messaging using TouchSystems' P15 32" Touch Monitor. This commercial-grade, large-format, interactive display offers a cost-conscious solution for digital signage applications with a fast, accurate touch, unaffected by surface contaminants such as liquids, dirt, dust and grime.

Corporate Communications

Prominently exhibit and edit graphs, charts and information, converting images from average to exceptional with this high-performance, touch display.

Military Applications

Exhibit and manipulate complex military charts and information with the touch of a finger.

Digital Display System

Provide a straight forward solution to sharing and displaying current information while reinforcing brand awareness.

Interactive Learning Stations

Display and edit educational content, creating a fresh and effective learning experience.

Specifications

Viewable Image Size	32"
Color	Black
Pixel Pitch	0.511mm
Brightness	500 cd/m2
Contrast Ratio	800:1
Viewing Angle	178° Vertical, 178° Horizontal
Response Time	9ms
Aspect Ratio	16:9
Vertical Synchronization	58-85 Hz
Touch Screen (Fully Integrated)	Surface Capacitive, Dispersive Signal Technology (DST) or Surface Acoustic Wave (SAW)
Connectivity Interfaces	USB or Serial (Touch); DVI-I, DVI-D and VGA 15-Pin D-Sub; DVI-D 24-Pin (HDCP), Analog 15 Pin D-Sub, Analog BNC, Composite (Shared RCA and BNC) or S-Video Component BNC (Y,Cb/Pb, Cr/Pr)
PC Compatibility (Touch Driver)	Windows 7, Vista ; XP; Server 2003; CE 2.12; 3.0; net (4.0, 5.0, 6.0); Linux (up to Kernel 2.6); Mac OS X
Display Resolution	1366 x 768 @ 60 Hz
Voltage Rating	AC 100-120V / AC 220-240V
Power Consumption	On: 120W; Power Savings Mode: < 5W
Dimensions (WxHxD)	31.1 in. x 21.2 in. x 9.7 in. (with Stand) 31.1 in. x 18.8 in. x 5.2 in. (without Stand)
VESA Hole Configuration	200mm x 200mm (4 Hole)
Limited Warranty	3 Years Parts and Labor including Backlight
Standards	FCC Class B, CE, UL, Energy Star, RoHS Compliant