



TouchSystems

P1 40" Touch Monitor

Information Display ■ Education ■ Corporate ■ Entertainment

At a Glance

Seamless Operation

3000:1 Contrast Ratio

Ultra-Thin Bezel

Multi-User Capability

Finger or Stylus Input

The professional-grade, high performance P1 40" Touch Monitor from TouchSystems offers sleek sophistication with bold visual impact. Boasting Full HD resolution, an expansion slot for emerging technologies, extensive communication options and eco-friendly features, this large-format touch display grabs attention while delivering sharp, touch-enabled messages.

Interactive Digital Signage

Reinforce brand awareness with sophistication while providing interactive, up to date information.

Educational Learning Stations

Display and edit educational content with ease, creating a more effective learning experience.

Corporate Communications

Improve the quality and impact of corporate communications by providing a distinct, visually engaging message on this cutting-edge display.

Entertainment Venues

Deliver clear and interactive messages, withstanding continuous use while dazzling spectators and engaging users.



Dispersive Signal Technology

P4050D-U1 - (USB)

P4050D-S1 - (Serial)

Protective Overlays

P40PA-1 - (Acrylic)

P40PG - 1 - (Chemically Strengthened Glass)

Contact Us

220 Tradesmen Dr.

Hutto, Texas 78634

1-800-320-5944

Sales@touchsystems.com

www.touchsystems.com

Specifications

Viewable Image Size	40"
Color	Black
Pixel Pitch	0.46mm
Brightness	650 cd/m ²
Contrast Ratio	3000:1
Viewing Angle	89° Vertical, 89° Horizontal
Response Time	8ms
Aspect Ratio	16:9
Vertical Synchronization	50-85 Hz
Touch Screen (Fully Integrated)	Dispersive Signal Technology (DST)
Connectivity Interfaces	DVI-D, Analog D-Sub, Analog BNC, Composite (Shared RCA and BNC), S-Video, HDMI, Component, Audio, Ethernet, RS-232 Communication
PC Compatibility (Touch Driver)	Windows 7, Vista, XP, Server 2003, CE 2.12, 3.0; .net (4.0, 5.0, 6.0); Linux (up to Kernel 2.6); Mac OS X
Display Resolution	1920 x 1080 @ 60 Hz
Voltage Rating	AC 100-120V / AC 220-240V
Power Consumption	On: 175W; Power Savings Mode: < 2W
Dimensions (WxHxD)	36.2 in. x 22.4 in. x 13.0 in. (with Stand) 36.2 in. x 21.0 in. x 5.5 in. (without Stand)
VESA Hole Configuration	300 x 300mm (4 hole)
Limited Warranty	3 Years Parts and Labor including Backlight
Standards	FCC Class B, CE, UL, Energy Star, RoHS Compliant