



TouchSystems

P15 42" Touch Monitor

Information Display ■ Education ■ Military ■ Corporate

At a Glance

Landscape and
Portrait Orientation

Public-Display-Grade
Panel

Excellent Touch
Positioning Accuracy

500 cd/m2 Brightness



Dispersive Signal Technology

P4250D-U - (USB)
P4250D-S - (Serial)

Protective Overlays

P42PA-15
Acrylic

P42PG-15
Chemically
Strengthened Glass

Contact Us

220 Tradesmen Dr.
Hutto, Texas 78634
1-800-320-5944

Sales@touchsystems.com
www.touchsystems.com

Transform digital signage while enhancing your surroundings with a high-performance P15 42" Touch Display from TouchSystems. This commercial-grade LCD monitor provides a quick and accurate response to touch and offers an interactive, cost conscious solution, resistant to surface contaminants such as liquids, dirt, dust and grime.

Corporate Communications

Improve corporate communications by providing a sharp, impactful message on this cutting-edge display.

Military Applications

Ideal for military training, these monitors allow complex charts and information to be presented with the touch of a finger.

Digital Display System

Catch attention and create impact with this high-definition touch display, combining touch and visual interest to increase the effectiveness of your message.

Interactive Learning Stations

Offer a new option in the classroom, creating a more interactive, visually interesting approach to learning.

Specifications

Viewable Image Size	42"
Color	Black
Pixel Pitch	0.681mm
Brightness	500 cd/m2
Contrast Ratio	800:1
Viewing Angle	178° Vertical, 178° Horizontal
Response Time	9ms
Aspect Ratio	16:9
Vertical Synchronization	58-85 Hz
Touch Screen (Fully Integrated)	Dispersive Signal Technology (DST)
Connectivity Interfaces	DVI-D 24-Pin (HDCP), Analog 15 Pin D-Sub, Analog BNC, Composite (Shared RCA and BNC) S-Video, Component BNC (Y,Cb/Pb, Cr/Pr)
PC Compatibility (Touch Driver)	Windows 7, Vista ; XP; Server 2003; CE 2.12; 3.0; net (4.0, 5.0, 6.0); Linux (up to Kernel 2.6); Mac OS X
Display Resolution	1366 x 768 @ 60 Hz
Voltage Rating	AC 100-120V / AC 220-240V
Power Consumption	On: 199W; Power Savings Mode: < 5W
Dimensions (WxHxD)	40.3 in. x 25.6 in. x 13.0 in. (With Stand) 40.3 in. x 24.2 in. x 5.2 in. (Without Stand)
VESA Hole Configuration	200mm x 200mm (4 Hole)
Limited Warranty	3 Years Parts and Labor including Backlight
Standards	FCC Class B, CE, UL, Energy Star, RoHS Compliant