



TouchSystems

S 40" Touch Monitor

Information Display ■ Entertainment ■ Medical ■ Corporate

At a Glance

Industrial Strength Design

4000:1 Contrast Ratio

Finger or Stylus Input

1080p HD resolution

Eco-Friendly Features



Dispersive Signal Technology

S4050D-U1 - (USB)
S4050D-S1 - (Serial)

Contact Us

220 Tradesmen Dr.
Hutto, Texas 78634
1-800-320-5944

Sales@touchsystems.com
www.touchsystems.com

The S 40" Touch Monitor from TouchSystems takes interactive digital signage to the next level with stunning visuals and full high definition. Ideal for corporate boardrooms, entertainment venues and hospitals, this professional display allows for 24/7 performance and is equipped with cutting edge energy saving options, an ambient light sensor and an advanced cooling system.

Interactive Digital Signage

Combine touch with visual interest to increase traffic and the effectiveness of your message.

Entertainment Venues

Catch attention 24/7 in any setting with prominent sophistication, interactivity and vibrant colors.

Health Care

Expand hospital messaging with interactivity allowing users to access donor information, health tips and hospital information.

Corporate Communications

Infuse intense hues and full motion, streaming video into corporate communications, awakening graphics and transmitting a stronger, clearer message.

Specifications

Viewable Image Size	40"
Color	Black
Pixel Pitch	0.46mm
Contrast Ratio	4000:1
Viewing Angle	89°/89°/89°/89°
Response Time	8ms (Gray-to-Gray)
Vertical Synchronization	50-85 Hz
Touch Screen (Fully Integrated)	Dispersive Signal Technology (DST)
Connectivity Interfaces	DVI-D, 15pin D-sub, Analog 5 BNC (RGB/HV), DisplayPort, Composite (Shared RCA/BNC), S-Video, HDMI Component BNC
PC Compatibility (Touch Driver)	Windows 7, Vista, XP, 2000, Server 2003, 95, 98, ME, NT4, CE 2.12, 3.0, .NET (4.0, 5.0, 6.0); MS DOS; QNX Linux (up to Kernel 2.6); iMac 9.0, OSX (Power PC, Intel CPU)
Display Resolution	1920 x 1080
Power Consumption	175W Typical
Dimensions (WxHxD)	38.7in. x 22.8in. x 5.5in.
VESA Hole Configuration	300 x 300mm (4 Hole)
Limited Warranty	3 Years Parts and Labor including Backlight
Standards	FCC Class B, CE, UL, Energy Star, RoHS Compliant