



TouchSystems

S 46" Touch Monitor

Information Display ■ Entertainment ■ Medical ■ Corporate

At a Glance

Industrial Strength Design

4000:1 Contrast Ratio

Finger or Stylus Input

1080p HD resolution

Eco-Friendly Features



Dispersive Signal Technology

S4650D-U1 - (USB)
S4650D-S1 - (Serial)

Contact Us

220 Tradesmen Dr.
Hutto, Texas 78634
1-800-320-5944

Sales@touchsystems.com
www.touchsystems.com

Turn heads and capture attention with the sophisticated S 46" Touch Monitor from TouchSystems'. Equipped with cutting edge energy saving options, an ambient light sensor and an advanced cooling system, the S 46" delivers digital signage in high definition with interactivity, perfect for high traffic spaces including entertainment venues, hospitals and corporate boardrooms.

Interactive Digital Signage

Increase traffic and the effectiveness of your message by combining touch with visual interest.

Entertainment Venues

Catch attention 24/7 in any setting with prominent sophistication, interactivity and vibrant colors.

Health Care

Expand hospital messaging with interactivity allowing users to access donor information, health tips and hospital information.

Corporate Communications

Infuse intense hues and full motion, streaming video into corporate communications, awakening graphics and transmitting a stronger, clearer message.

Specifications

Viewable Image Size	46"
Color	Black
Pixel Pitch	0.56mm
Contrast Ratio	4000:1
Viewing Angle	89°/89°/89°/89°
Response Time	8ms (Gray-to-Gray)
Vertical Synchronization	50-85 Hz
Touch Screen (Fully Integrated)	Dispersive Signal Technology (DST)
Connectivity Interfaces	DVI-D, 15pin D-sub, Analog 5 BNC (RGB/HV), DisplayPort, Composite (Shared RCA/BNC), S-Video, HDMI Component BNC
PC Compatibility (Touch Driver)	Windows 7, Vista, XP, 2000, Server 2003, 95, 98, ME, NT4, CE 2.12, 3.0, .NET (4.0, 5.0, 6.0); MS DOS; QNX Linux (up to Kernel 2.6); iMac 9.0, OSX (Power PC, Intel CPU)
Display Resolution	1920 x 1080
Power Consumption	210W Typical
Dimensions (WxHxD)	43.8in. x 25.8in. x 5.5in.
VESA Hole Configuration	300 x 300mm (4 Hole)
Limited Warranty	3 Years Parts and Labor including Backlight
Standards	FCC Class B, CE, UL, Energy Star, RoHS Compliant