



TouchSystems

# P20 19" Touch Monitor

Banking

Corporate

Retail

Medical

## At a Glance

4-Way Ergonomic Stand

1500:1 Contrast Ratio

Self-Adjusting Light Sensor

Three Optional Video Inputs



## Resistive

P1990R-U - (USB)  
P1990R-S - (Serial)

## Capacitive

P1950C-U - (USB)  
P1950C-S - (Serial)

## Surface Acoustic Wave (SAW)

P1920S-U - (USB)  
P1920S-S - (Serial)

## Contact Us

220 Tradesmen Dr.  
Hutto, Texas 78634  
1-800-320-5944

Sales@touchsystems.com  
www.touchsystems.com

Providing impeccable performance, TouchSystems' P20 19" Touch Monitor offers a sensitive touch, rich colors and Rapid Response video technology. Ideal in almost any space, this professional display is ergonomically friendly and self-adjusts its brightness to suit changing lighting conditions.

## Corporate Solution

Create an efficient workspace, maximizing productivity while maintaining maximum comfort with its ergonomic design.

## Banking and Finance

Deliver real time information from the bank lobby to the trading room floor, featuring superior Rapid Response performance and intense color contrasts.

## Health Care

Link doctors and medical staff together with the seamless flow of information, offering interactive solutions for medical applications.

## Retail Sales

Provide an outstanding customer experience, exceeding expectations by operating more effectively.

## Specifications

<b>Viewable Image Size</b>	19.0"
<b>Color</b>	Black
<b>Pixel Pitch</b>	0.294mm
<b>Brightness</b>	250 cd/m2
<b>Contrast Ratio</b>	1500:1
<b>Viewing Angle</b>	89° Vertical, 89° Horizontal
<b>Response Time</b>	25ms
<b>Aspect Ratio</b>	4:3
<b>Vertical Synchronization</b>	56-75 Hz
<b>Touch Screen (Fully Integrated)</b>	Resistive, Capacitive, Surface Acoustic Wave (SAW)
<b>Connectivity Interfaces</b>	DVI-D, DVI-I and VGA 15-pin D-Sub
<b>PC Compatibility (Touch Driver)</b>	Windows 7, Vista, XP, 2000, Server 2003, 95, 98, ME, NT4, CE 2.12, 3.0, .NET (4.0, 5.0, 6.0); Linux (up to Kernel 2.6); MS DOS; iMac 9.0, OS X (Power PC, Intel CPU); QNX
<b>Display Resolution</b>	1280 x 1024 @ 60 Hz
<b>Voltage Rating</b>	AC 100-120V / AC 220-240V
<b>Power Consumption</b>	On: 39W; Power Savings Mode: 1W
<b>Dimensions (WxHxD)</b>	15.8 in. x 14.4-19.5 in. x 9.7 in. (with Stand) 15.8 in. x 13.0 in. x 3.1 in. (without Stand)
<b>VESA Hole Configuration</b>	100mm x 100mm
<b>Limited Warranty</b>	3 Years Parts and Labor including Backlight
<b>Standards</b>	FCC Class B, CE, UL, Energy Star, RoHS Compliant