



# WTE-Series 22" Touch Monitor

Retail • Education • Government • Hospitality • Corporate



**WTE2290R-D**  
5-Wire Resistive

### Contact Us

220 Tradesmen Dr.  
Hutto, TX 78634  
512-846-2424

Sales@touchsystems.com  
www.touchsystems.com

The TouchSystems WTE-Series 22" Wide Screen Touch Monitor combines elegance with durability, making it the perfect touch monitor to meet your needs. Designed for high-standard touch application, the TouchSystems WTE 22" is compact in size but not in features, providing a touch screen solution that won't break the bank. Its dust- and splash-proof design make this an ideal monitor for public or high-use applications, and its versatile mounting design make it a great fit for most any environment. The TouchSystems WTE 22" is also HID compliant, making integration with thin clients or computers a breeze. With a lockable OSD button and 8-language support, the TouchSystems WTE 22" packs a big punch in compact size.

#### Retail

The TouchSystems WTE 22" Touch Monitor has an optional integrated magnetic strip reader (MSR), making it the perfect retail solution.

#### Education

Compact and economical, the TouchSystems WTE 22" elevates any classroom, cafeteria or service area to the next level.

#### Government

From senate chambers to the DMV, the TouchSystems WTE 22" brings versatility, usability and elegance to any government environment.

#### Hospitality

From wowing your guests to driving foot traffic, the TouchSystems WTE 22" Touch Monitor is sure to meet your needs.

#### Corporate

From the front desk to the board room, give visitors and employees a beautiful touch screen solution that's sure to please.

Viewable Image Size	22"
Color	Dark Gray
Pixel Pitch	0.294mm
Brightness	240 cd/m <sup>2</sup>
Contrast Ratio	1000:1
Viewing Angle	160° Vertical, 160° Horizontal
Response Time	5 ms
Display Color	16.7M (6 bits + Hi-FRC)
Vertical Synchronization	75 Hz
Touch Screen (Fully Integrated)	5-Wire Resistive
Connectivity Interfaces	D-Sub 15-pin, Dual Serial/USB
PC Compatibility (Touch Driver)	Windows 7, Vista, XP, 2000, NT4, ME, 98, 95, XP Tablet PC, Embedded XP, Windows CE 2.13, 3.0, .net, 6.0, Debian, Fedora, Mandrake, RedHat, SuSE, Mac OS9, OSX, DOS-DOS
Display Resolution	1920 x 1080 @ 60 Hz
Voltage Rating	Embedded DC 12V, 4.16A
Power Consumption	Operating: 42W, Sleep: 3W, Off: 1W
Dimensions (WxHxD)	538.5mm x 383.8mm x 287.14mm (with stand)
Net Weight	23.15 pounds
VESA Hole Configuration	100mm x 100mm, portrait and landscape
Operating Temperature	32°F ~ 104°F
Storage Temperature	-4°F ~ 140°F
Standards	TUV, CE, UL, CUL, FCC-B, RoHS, IPX1
Limited Warranty	3 Years Parts and Labor